



**Manali Petrochemicals Limited.,**  
Ponneri High Road, Manali, Chennai -600 068  
Ph: 25941557/3910/1025 FAX: 25941199

Revision No.: 1

Date of issue: 2015

Sheet 1/1

## **PRODUCT DATA SHEET**

### **EMPEYOL E4022**

#### **DESCRIPTION**

EMPEYOL E4022 is a 4000 molecular weight, polyether diol containing a high percentage of primary hydroxyl groups. It is used in several urethane applications – most notably in high resilience moulded foams and also in semi-flexible foams and RIM elastomers.

#### **SALES SPECIFICATION**

Characteristics	Unit	Specification
Appearance	-----	Clear viscous liquid
Density at 25 °C	g/cc	1.030- 1.035
Viscosity at 25 °C	Cps	700 - 900
Water	% w/w	0.50 maximum
Hydroxyl Number	MgKOH/g	26.0 – 30.0

**PACKING SIZE** : 210 / 25 kg nett.

#### **STORAGE AND HANDLING**

- EMPEYOL E 4022 polyol is to be stored in tightly closed containers preferably at temperatures between 30 –35 °C.
- Should wear gloves and goggles during handling.
- Shelf life : 1 year

#### **HEALTH AND SAFETY ADVICE**

EMPEYOL E 4022 polyol should present no unusual health problems when used in manufacturing operations where satisfactory standards of personal and industrial hygiene are maintained. Precautions should be taken to avoid exposure to the eye or prolonged contact with the skin.

---

The information in this data sheet is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond the company's control. MPL disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other materials or in any process.

---