

Ponneri High Road, Manali,  
Chennai - 600068

Ph: +91 44 25941025/1421/1557

Fax: +91 44 2594 1199

Email: [mkt@manalipetro.com](mailto:mkt@manalipetro.com)

[www.manalipetro.com](http://www.manalipetro.com)



## PRODUCT DATA SHEET

### EMPEYOL F6080/2F6080

#### DESCRIPTION

EMPEYOL F6080/2F6080 is a 6000 molecular weight, trihydroxy polyether polyol containing a high percentage of primary hydroxyl groups. It is used as a cell opener in urethane applications

#### SALES SPECIFICATION

Characteristics	Unit	Specification
Appearance	---	Clear viscous liquid
Viscosity at 25 °C	cps	1600±300
Density @25°C	g/cc	1.080 – 1.100
Hydroxyl Number	mgKOH/g	26.0 – 30.0
Water	% w/w	0.20 maximum

**PACKING SIZE :** 210 / 25 kg nett.

#### STORAGE AND HANDLING

EMPEYOL F6080/2F6080 polyol is to be stored in tightly closed containers preferably at temperatures between 20 –35 °C.(At low temperature product may appear slightly cloudy)  
Should wear gloves and goggles during handling.

**Shelf life :** 1 year

*Ponneri High Road, Manali,  
Chennai - 600068*

*Ph: +91 44 25941025/1421/1557*

*Fax: +91 44 2594 1199*

*Email: [mkt@manalipetro.com](mailto:mkt@manalipetro.com)*

*[www.manalipetro.com](http://www.manalipetro.com)*



## ***PRODUCT DATA SHEET***

### **HEALTH AND SAFETY ADVICE**

EMPEYOL F6080/2F6080 polyol should present no unusual health problems when used in manufacturing operations where satisfactory standards of personal and industrial hygiene are maintained. Precautions should be taken to avoid exposure to the eye or prolonged contact with the skin.

---

The information in this data sheet is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond the company's control. MPL disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other materials or in any process.

---