Ponneri High Road, Manali, Chennai - 600068

Ph: +91 44 25941025/1421/1557

Fax: +91 44 2594 1199

Email: mkt@manalipetro.com www.manalipetro.com



PRODUCT DATA SHEET

EMPEYOL HSR 200/6XF

DESCRIPTION:

EMPEYOL HSR 200/6XF is an eco-friendly CFC free formulated polyether polyol to be used in combination with **POLYMERIC MDI** or equivalent isocyanate for the production of polyurethane rigid foams for pipe sections. This polyol has been preblended with HCFC – 141b. "X" implies the presence of fire retardant in the formulated polyol.

SALES SPECIFICATION

Characteristics	Unit	Specification
Color and appearance		Yellow to brown liquid
Viscosity at 25°C	(cps)	200 - 300
Density at 25 ^o C	(grams/cc)	1.140 ± 0.03
RECOMMENDED PROCESSING		
CONDITIONS		
Mixing ratio(Polyol: Isocyanate-		100 : 115
Wannate 8018)		
Temperature		20 - 25
Polyol	0	20 - 25
Isocyanate	(⁰ C)	
REACTION PROFILE USING		
BENCH MIXER AT 21° C(*)		
Mix ratio [Polyol : Iso]		
Cream time	(pbw)	100 : 115
Gel time	(seconds)	20 ± 02
	(seconds)	80 - 100

Revision No: 3 Date of Issue: Mar 2011

Ponneri High Road, Manali, Chennai - 600068

Ph: +91 44 25941025/1421/1557

Fax: +91 44 2594 1199

Email: mkt@manalipetro.com www.manalipetro.com



PRODUCT DATA SHEET

Free rise density	(kg/cu.m)	22.0 - 24.0
Demould time	(minutes)	7 (minimum)
PROPERTIES OF THE FOAM:		
Overall density	(lzg/ou m)	40.0 45.0
Flammability test for Foam :Horizontal burning characteristics	(kg/cu.m)	40.0 - 45.0
as per IS :11239 – part 12-1988		
K value	(mm)	60 (maximum)
	(W/m.K)	0.020 (maximum)

(*) Depending on customer's requirement, reactivity can be altered and supplied.

PACKING SIZE: 210 kg Nett/25kg Nett

HANDLING & STORAGE:

EMPEYOL HSR 200/6XF and POLYMERIC MDI (or) EQUIVALENT ISOCYANATE should be stored in tightly closed containers at temperature between 20°C and 30°C and should not be exposed to direct sunlight.

Shelf life: 6 months.

HEALTH & SAFETY ADVICE:

EMPEYOL HSR 200/6XF and POLYMERIC MDI or equivalent isocyanate should present no hazard in manufacturing operations where satisfactory standards of personal and industrial hygiene are maintained. Precautions should be taken to avoid exposure to the eye or prolonged contact with skin.

The information in this data sheet is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond the company's control. MPL disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other materials or in any process.

Revision No: 3 Date of Issue: Mar 2011

Ponneri High Road, Manali, Chennai - 600068

Ph: +91 44 25941025/1421/1557 Fax: +91 44 2594 1199

Email: mkt@manalipetro.com www.manalipetro.com



PRODUCT DATA SHEET

Revision No: 3 Date of Issue: Mar 2011