

**EMPEYOL VE3780 B****PRODUCT DESCRIPTION:**

**EMPEYOL VE3780 B** polyol is designed for production of slabstock polyurethane foams and speciality applications. Typical foam applications include conventional Viscoelastic types. It is compatible with most polyether polyols and can be blended with other diols and triols to achieve desirable modification of product properties.

**PROPERTIES OF THE POLYOL:**

Property	Specification
Hydroxyl number, mg KOH/g	210 ± 20
Water, Wt % (max)	0.2 %
colour	Clear liquid

**TYPICAL PROPERTIES:**

Property	Specification
Appearance	Clear liquid
Specific gravity @ 20Deg C	1.02±0.02
Viscosity @ 25 Deg C , cps	275 ± 50

**HANDLING & STORAGE:**

**Empeyol VE3780B** is a hygroscopic and may absorb water. Containers should be stored in tightly closed container & should not be exposed to direct sunlight. It should be preferably stored at temperatures between 20 °C TO 35°C.

**HEALTH & SAFETY ADVICE:**

**EMPEYOL VE3780 B** should present no hazard in manufacturing operations where satisfactory standards of personal and industrial hygiene are maintained. Precautions should be taken to avoid exposure to the eye or prolonged contact with skin.

**SHELF LIFE:**

Shelf life under specified storage conditions is 1 year.

**PACKING:**

210 / 25 kg nett.

**Warning:** This information is believed to be accurate but all recommendations are made without warranty, since the conditions are beyond the company's control. MPL disclaims any liability in connection with the use of information, and does not warrant against infringement by reason of the use of any of its products in combination with other materials or in any process.