



Manali Petrochemicals Limited.,
Ponneri High Road, Manali, Chennai -600 068
Ph: 25941557/3910/1025 FAX: 25941199

Revision No. : 1

Date of issue: April 2012

Sheet 1/1

PRODUCT DATA SHEET

EMPEYOL R444

DESCRIPTION

EMPEYOL R 444 is a rigid grade OTDA-based polyol, suitable for the formulation of polyol system for Rigid Polyurethane applications. Especially for appliance and fast curing system.

SALES SPECIFICATION

Characteristics	Unit	Specification
Appearance	----	Dark brown viscous liquid
Viscosity@25°C	cps	8000 - 10000
Density @25°C	g/cc	1.040-1.060
Hydroxyl Number	mgKOH/g	430 +/-10
Water	% w/w	0.20 maximum

PACKING SIZE : 210 kg nett.

STORAGE AND HANDLING

- EMPEYOL R444 polyol is to be stored in tightly closed containers preferably at temperatures between 20 –35 °C.
- Should wear gloves and goggles during handling.
- Shelf life : 1 year

HEALTH AND SAFETY ADVICE

Empeyol R444 polyol should present no unusual health problems when used in manufacturing operations where satisfactory standards of personal and industrial hygiene are maintained. Precautions should be taken to avoid exposure to the eye or prolonged contact with the skin.

The information in this data sheet is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond the company's control. MPL disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other materials or in any process.
